




Dimensions

| | |
|-------------------------|--------------|
| Product dimensions (mm) | 37 x 50 x 80 |
|-------------------------|--------------|

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 2,8 |
| Real luminous flux (Lm) | 115,2 |
| Luminous efficiency (Lm/W) | 41,1 |
| Beam angle (°) | 25 |
| IP | 20 |
| Electrical class insulation | Class 1 |
| Photobiological risk | 0 - Exempt |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Stainless steel |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 2,5 |
| Nominal luminous flux (Lm) | 150 |
| Colour temperature (K) | 3000 |
| CRI | 80 |

Decorative minimalist sconce from the TROLL family Flex.

DESCRIPTION

Decorative minimalist sconce from the TROLL family Flex setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as Lighting hotel rooms. Designed for wall surface mounted. Luminaire body made from stainless steel sheet finished in chromed. Luminaire built-in a Polycarbonate opal diffuser with an angle beam of 120°. Luminaire sets a 2,5 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 115,2 Lm, with an efficiency of 41,1 Lm/W and a total consumption of 2,8 W. The average life for the luminaire is h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|---|
| Item code | 0170/1/20 |
| Product type | IN |
| Category | Apliques |
| Family | Flex |
| Subfamily | Flex |
| Materials | Luminaire body made from stainless steel sheet. |
| Optical system | Luminaire built-in a Polycarbonate opal diffuser. |
| Installation instructions | Luminaire designed for wall surface mounted. |

Pictograms

