


**Dimensions****Product dimensions (mm)** 50 x 574 x 60**Scheme****Scheme****Product**

Real power (W)	9
Real luminous flux (Lm)	980
Luminous efficiency (Lm/W)	109
Life time (h)	60000
IP	44
IK	4

**Electrical class insulation** Class 1**Operating temperature** from 5°C to 30°C**Electrical feeding** 220..240V, 50/60Hz**Colour** Anodized aluminum**Diffuser** PMMA opal diffuser**Control gear****Control gear included** Yes**Control gear** Electronic Control Gear**Light source****Light source included** Yes**Light source** Led**Nominal power (W)** 8**Nominal luminous flux (Lm)** 1349**Average life time (h)** 60000**Colour temperature (K)** 3000**Colour consistency (SDCM)** 3**CRI** 80**Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED.****DESCRIPTION**

Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED. This fixture is recommended for hospital bathrooms and wards. Luminaire body made from aluminium profile. Luminaire set diffuser made from plastic with asymmetric optical system which provides high energetic efficiency.

Item code	0E1XK9L10BPLX
Product type	IN
Category	Apliques
Family	X-Line
Subfamily	X-Wall K9 Led
Materials	Luminaire body made from aluminium profile with diffuser made from plastic.
Optical system	Luminaire set a diffuser made from plastic with asymmetric optical system.
Installation instructions	Luminaire designed to be wall surface mounted.

**Pictograms**