


Dimensions

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 2 x 1,9 |
| Real luminous flux (Lm) | 214 |
| Luminous efficiency (Lm/W) | 58 |
| Beam angle (°) | 2 x (9 x 36) |
| Life time (h) | 50000 |
| IP | 20 |
| IK | 04 |
| Electrical class insulation | Class 1 |
| Operating temperature | from 5°C to 30°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Grey |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | LED |
| Nominal power (W) | 3,4 |
| Nominal luminous flux (Lm) | 304 |
| Average life time (h) | 50000 |
| Colour temperature (K) | 3000 |
| Diameter (mm) | 50000 |
| Colour consistency (SDCM) | 5 |
| CRI | 80 |
| TM30RF | 80 |

Decorative sconce from the TROLL family Mini wall C Led.

DESCRIPTION

Decorative sconce from the TROLL family Mini wall C Led. Luminaire made from Aluminium with lenses of renowned producers which allows unlimited possibilities to arrange luminous flux up and down. MINI WALL C LED is recommended to be installed as a decorative and accent Lighting in both indoor and outdoor façades.

| | |
|---------------------------|--|
| Item code | 0KFL21-2 |
| Product type | IN |
| Category | Apliques |
| Family | Mini Wall |
| Subfamily | Mini Wall Led |
| Materials | Luminaire body made of aluminium with plastic lenses. |
| Optical system | The fixture sets an optical system based on lenses which produce a double beam 9° x 36°. |
| Installation instructions | Luminaire designed to be wall surface mounted. |

Pictograms

