


**Dimensions**

Product dimensions (mm)	Ø289 x 372
Packing dimensions (mm)	390 x 390 x 475
Net weight (g)	8000
Gross weight (Kg)	9,8

Scheme**Scheme**

Industrial highbay luminaire from the TROLL family Campana.

DESCRIPTION

Industrial highbay luminaire from the TROLL family Campana setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general lighting of warehouses, supermarkets, exhibition pavilions and other indoor industrial areas. Designed for Ceiling suspended installation. Body built in die-cast aluminium and polycarbonate finished in grey. Luminaire is IP65. Luminaire built-in an diffuser made of synthetic material with an angle beam of 120°. Luminaire sets a 300 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 28870 Lm, with an efficiency of 96,2 Lm/W and a total consumption of 300 W. The average life for the luminaire is 35000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	5010/L384/21
Product type	IN
Category	Industrial
Family	Highbays
Subfamily	Campana
Materials	Body built in die-cast aluminium and polycarbonate.
Optical system	Luminaire built-in a diffuser made of synthetic material.
Installation instructions	Luminaire designed for Ceiling suspended installation.

Pictograms**Product**

Real power (W)	300
Real luminous flux (Lm)	28870
Luminous efficiency (Lm/W)	96,2
Beam angle (°)	110
Life time (h)	35000
IP	44
Electrical class insulation	Class 1
Operating temperature	from -20°C to 40°C
Electrical feeding	100..240V, 50/60Hz
Colour	Grey
Energy efficiency class	A+

Control gear


Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,99

Light source

Light source	Led
Nominal power (W)	270
Nominal luminous flux (Lm)	30000
Average life time (h)	35000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

Photometry

Photometry



Accessories

5010/60/21

Reflector 60°.

5010/90/21

Reflector 90°.

Scheme

