





Dimensions		
Product dimensions (mm)	ø500	
Packing dimensions (mm)	505 x 505 x 505	
Net weight (g)	14200	
Gross weight (Kg)	15,8	

Scheme

Scheme

Lamp



Architectural bollard from the TROLL family Riddle.

DESCRIPTION

Architectural bollard from the TROLL family Riddle optimised to be used as lighting Architectural boliard from the LROLL family Riddle optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for to be floor fixed. Luminaire body built in die-cast aluminium finished in grey. Luminaire Built-in a matt diffuser with an angle beam of floor washer. Luminaire is IP65 and IK10. Use HIT-T of 79 W lightsource. Lamp not included. Luminaire Built in a ON/OF fed at 220-240V; 50/60 Hz.

Item code	6600/70/21
Product type	OUT
Category	Bollards
Family	Riddle
Subfamily	Riddle
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a matt diffuser.
Installation instructions	Luminaire designed for to be floor fixed.

Pictograms







Real power (W)	79
IP	65
IK	10
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220240V, 50/60Hz
Colour	Grey
Energy efficiency class	A

Control gear included	Yes	
Control gear	Electronic Control Gear	
Light source		
Light source	Discharge	
Lamp holder	G12	
Nominal power (W)	70	
Nominal luminous flux (Lm)	6600	
Average life time (h)	6000	
Voltage (V)	220	
Diameter (mm)	19	

HITT